

AERO-TACK 20 oz.

AEROSOL DUCT LINER and GENERAL PURPOSE ADHESIVE Fast Tacking • Variable Pattern • Adjustable Spray



Recommended Uses	Use AERO-TACK as an adhesive to position and hold all types of insulation to metal, fiberglass, paper and wood. May also be used to bond to a variety of different substrates.
Application	Apply AERO-TACK to clean substrate, holding container 6 to 8 inches from surface. Apply full, even coats.
Dry Time	Tack is immediate. Open time is approximately 10 minutes.
Temperature Limits	Storage and application... 20°F to 100°F Service..... -30°F to 200°F
Color	Clear
Packaging	20 oz. (12 oz. net wt.) aerosol can
Precautions	Flammable. Contents under pressure. Use only in well ventilated area. Keep away from heat and fame. Avoid prolonged exposure to vapor. Avoid contact with skin or eyes. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. In case of eye contact, flush thoroughly for at least 15 minutes and get medical attention.
Clean Up	Use mineral spirits or similar solvent with appropriate safety precautions.

AERO-TACK 12, 40, 355

SELF-CONTAINED CANISTER GUN & HOSE NON-FLAMMABLE INSULATION ADHESIVE



Recommended Uses	Use AERO-TACK as an adhesive to position and hold all types of insulation to metal (galvanized, aluminum, stainless). Pin according to SMACNA requirements.
Application	Apply AERO-TACK , using Polymer Adhesives spray hoses and gun, to clean sheet metal in preparation for placement of insulation.
Spray Gun	Airless gun with .065 tip and Teflon seals
Hoses	6 ft. and 12 ft. lengths
Dry Time	Tack is immediate. Open time is approximately 15 minutes.
Temperature Limits	Storage and application... 20°F to 100°F Service..... -30°F to 200°F
Coverage	Approximately 90 - 100 sq. ft. per lb.
Soilds Content / Weight per Gallon	14.7% ± 0.2% by weight / 8.4 lbs. ± 0.4 lbs. per gallon
Color	Blue
Fire Hazard Classification	<p style="text-align: center;">SURFACE BURNING CHARACTERISTICS</p> <p style="text-align: center;">Flame Spread5 Smoke Developed5</p> <p style="text-align: center;">When tested in accordance with the requirements of UL 723, ASTM E-84, NFPA 225. AERO-TACK satisfies the requirements of NFPA 90A and 90B.</p>
Packaging	12# & 40# Pressurized Canister
Precautions	Flammable. Contents under pressure. Use only in well ventilated area. Keep away from heat and fame. Avoid prolonged exposure to vapor. Avoid contact with skin or eyes. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. In case of eye contact, flush thor - oughly for at least 15 minutes and get medical attention.
Clean Up	Use mineral spirits or similar solvent with appropriate safety precautions.



POLYMER ADHESIVES

SEALANT SYSTEMS, INC.

www.polymeradhesives.com

501 Garrett Morris Parkway, Mineral Wells, TX 76067 (888) 721-SEAL Fax (888) 921 7325