

POLY-SCRIM™

FIBERGLASS MESH REINFORCEMENT TAPE



FEATURES

- *High tensile strength*
- *Use indoors and outdoors*
- *Use to bridge gaps*
- *Excellent for duct board joint reinforcement*
- *Increases pressure ratings*
- *Satisfies the requirements of UL 181 A-M*
- *Mold and mildew resistance*

TECHNICAL SPECIFICATIONS

Packaging	POLY-SCRIM 3" x 150' rolls, 24 per case POLY-SCRIM+ 3" x 150' rolls, 24 per case
Shelf Life	Unlimited in dry environment
Cure Time	Does not effect manufacturers' recommended cure time
Color:	POLY-SCRIM White POLY-SCRIM+ Blue
Temperature Limits	Storage and application... no special requirements Service..... -40°F to 500°F
Weave	20 x 10 threads per inch (25 mm) ± 1 thread
Specification Compliance	ASTM D-1668, Type III, Federal Spec. HH-C-466, UL 181 AM Reinforcement Tape

DESCRIPTION

POLY-SCRIM is a woven fiberglass membrane that is flexible and will conform to irregular surfaces. It is used as a reinforcing membrane providing exceptional tear resistance and durability. **POLY-SCRIM+** has a pressure sensitive adhesive on back side for holding tape in place for easier application purposes.

RECOMMENDED USES

POLY-SCRIM and **POLY-SCRIM+** can be used as a reinforcing membranes with HVAC duct sealants and thermal insulation coatings to provide extra strength and coating uniformity. Excellent for bridging gaps where joints do not meet exacting tolerances.

APPLICATION INSTRUCTIONS

Apply to clean, dry surfaces, free from oils, greases, dirt, and foreign matter. Apply **POLY-SCRIM** sealant or coating over the base coat and scrim tape at manufacturers recommended wet film thickness. **POLY-SCRIM** and **POLY-SCRIM+** has a pressure sensitive backing to hold the scrim in place prior to applying sealant for coatings. This eliminates the need for a tack coat.

Polymer Adhesives Sealant Systems Inc., is proud to be affiliated with the following organizations:



POLYMER ADHESIVES
SEALANT SYSTEMS, INC.

www.polymeradhesives.com